

タイプ及び嵌合方式	品名	表面色 ※	シート部								遮蔽材			ホック材質 ※	難燃規格		
			シート部厚み	適用温度特殊 ※	塩ビフリー	耐熱	耐電圧	屈曲性	車材燃試	UL94 非登録※ VTM-0相当品/UL	アルミ	メッシュ	導電布				
ジッパータイプ	Zトラック		SHNJ	0.43mm						●	●	70μm					
			SHNF(AR)	0.28mm						●	●	20μm					
			SHNF	0.24mm							●		10μm				
			SHNX	0.24mm							●		10μm	2層			
			SHNS	0.24mm							●		10μm		●		
			SHNJX(2)	0.43mm						●	●	70μm	2層				
			SHNJX(4)	0.43mm						●	●	70μm	4層				
			SHX(2)	0.34mm						●	●			2層			UL224 VW-1
			SHX(4)	0.34mm						●	●			4層			UL224 VW-1
			ZTZX(2)	0.5mm	●		●	●						2層			
			ZTZX(4)	0.5mm	●		●	●						4層			
	Rトラック		RTF-500	0.24mm						●	10μm						
ホックタイプ			OTF	0.24mm						●	10μm			●			
			OTFX	0.24mm						●	10μm	2層		●			
			OTFS	0.24mm						●	10μm		●	●			
			OTEF	0.24mm		●				●	●	10μm			●		
マジックタイプ			MTF	0.24mm						●	10μm						
			MTF(ARK)	0.28mm						●	●	20μm					
			MTFX	0.24mm						●		10μm	2層				
			MTFS	0.24mm						●		10μm	2層	●			
			MTEF	0.24mm		●				●	●	10μm					
			MTX(B)	0.34mm						●	●		2層				
			MTX(G)	グレー	0.34mm					●	●		2層				
			MTS(B)		0.34mm					●	●			●			
			MTS(G)	グレー	0.34mm					●	●			●			
テープタイプ			DK-800										●				
スリーブタイプ		シルバー	ZSK-HF			●	●		●	●						UL1441 VW-1	
		シルバー	ZSK-BF			●	●		●	●							
熱収縮タイプ			SSチューブ			●							●		UL224 VW-1 (熱収縮チューブ部)		

※定尺内に繋ぎがある場合があります。

適用温度特殊 ※ 各製品ページをご確認ください(一般適応温度 -15℃~+60℃)

表面色 ※ 記載無しは黒色

UL94 VTM-0相当品/UL非登録 ※ 自社解析結果

ホック材質 ※ ●ポリアセタール ○ナイロン ◎ステンレス